



507 Willoughby Rd
Willoughby 2068
NSW

Mo Tu We Fr 10 to 5.30
Th 10 to 7.00
Sa 9.30 to 3.00

TEL: (02) 9958 0412
FAX: (02) 9958 2341
email: sales@ecoathome.com.au
web: www.ecoathome.com.au

BIO NATURAL TIMBER OIL CLEAR EXTERIOR

DESCRIPTION:

A penetrating and finishing oil, which deepens and enhances the natural grain of the timber. It is resistant to dirt and moisture. Suitable for exterior paneling, garden furniture, windows, sandpits, box framing, rafters, pergolas etc. Not to be used on alkaline surfaces, plaster, concrete or fibro-cement. If considering use on those materials a test-strip should be made to assess suitability.

PROTECTION:

Protects against weather and wood-destroying ultra-violet light. One to three coats are recommended depending on the absorbency of the timber. Box frames, timber windows, cladding, rear side and end grains must be treated

BEFORE INSTALLATION

PREPARATION:

Prepare surface in accordance with AS 2311 Painting of Buildings. Wood and other surfaces should be well sanded, dry and cleaned of greasy, waxy and dirty contaminants using BIO Thinner. Old coats must be removed. Hardwoods and other timbers rich in natural oils, waxes, acids and terpenes should be degreased using BIO Thinner, because these substances may mix with the oil and prolong its drying time.

For fungi and insect treatment use BIO WOOD PROTECTING BORAX. Before painting, wipe off the surplus of Borax with a damp cloth; otherwise surface residue may inhibit paint adhesion.

APPLICATION:

Stir thoroughly before use with a broad flat stirrer. Brush, roll or spray thinly and evenly working the oil well into the grain. Thick coats wrinkle when dry. Avoid bubbles. If necessary thin with BIO THINNER for hardwood application. Do not apply more oil than the surface can absorb. Remove excess oil with a dry, lint free cloth after approx. 1 - 2 hours. Lightly sand between coats if necessary with fine sandpaper. Allow 12 to 24 hours to dry between coats. Low temperatures and humid conditions prolong the drying time. Apply second and subsequent coats only after previous coat has thoroughly dried. Do not use below +10 C and or above 80% humidity or in cold damp conditions, or when condensation, rain, dew or frost is likely to occur. Provide adequate ventilation during application and drying. Reaches maximum durability after 8-14 days

RE-COATING:

Re-coating is recommended after approximately 12 - 24 months, depending on the exposure to the weather or to those areas seen to be necessary

INGREDIENTS:

Based on linseed oil, wood oil, UV-protector, paraffin oil, lemon peel oil, pine oil, Lead free drying agents

CLEANING:

Clean with BIO Thinner

COVERAGE:

1 Litre covers approx. 5-10 sqm 1st coat on softwood
8-10 sqm 2nd coat on softwood
8-10 sqm on hardwood

PACKAGING:

1, 4 and 20 Litres

PRECAUTION:

Keep away from open flames and out of reach of children. Do not misuse. Please dispose of used rags in a sealed metal container. Can spontaneously combust.

STORAGE:

Keep tightly sealed in a cool and dry place. Surface film may develop in opened cans.

BIO NATURAL TIMBER OIL is an environmentally friendly product.

1/07/2005

The preceding information is given as a general guide only. Some variations may occur or be advisable for particular conditions. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.

Quality paints, oils and varnishes
Healthy cleaning and household
Luxury organic bed linen
Gentle baby care
Biodegradable bags and tableware

Printed on 100% recycled paper

Water and energy saving
Select books, stationery and gifts
Natural personal care
Guilt-free disposable nappies
Really green gardening