

507 Willoughby Road, Willoughby NSW 2068 Mon – Fri 10 to 5.30 Sat 9.30 to 4.00 sales@ ecoathome.com.au www.ecoathome.com.au

Tel: 02 9958 0412 Fax: 02 9958 2341

volvox



Technical Information Sheet - September 2007

VOLVOX Wax Finish is a natural protective coating made from water-borne Carnauba wax. It is formulated for sealing furniture, floors and painted surfaces. Furthermore it is suitable for the care and maintenance of oiled and waxed floors.

Properties

VOLVOX Wax Finish produces a vapour permeable but water resistant film that can be buffed to an attractive, soft sheen.

Uses

For protecting and maintaining heavily-used oil finished surfaces such as timber floors, cork, natural stone or tiled floors, stairs, work surfaces etc.

Specification Data

Colour: Clear Finish: Satin

Drying Time: 15 minutes

Coverage:

Undiluted approximately 25 square metres per litre
Diluted - 1 litre will make 20-50 litres when mixed with water

Flash Point: None (Nonflammable) Pack Size: 1 litre

Storage:

Keep container tightly sealed and store in a cool, dry and frostfree place.

Shelf Life: 24 months for unopened containers.

Application Data

Method: Cloth or mop Thinning: Water Cleaning: Water

Surface Condition

Dry, clean and firm. Best results are on oil finished surfaces such as either VOLVOX Hard Oil Wax Finish (1-342), VOLVOX Hard Oil (1-340) or VOLVOX Wood Oil (1-346).

Directions

Shake container well before use.

Protect and Seal Surfaces:

Use undiluted and apply evenly with a water-wet cloth or mop. Leave for up to 15 minutes, then buff with dry lint-free cloth or buffing machine (white pad).

Maintenance:

Mix 20-50 ml of VOLVOX Wax Finish into 10 litres of warm water. Apply as above.

Note:

Using micro-fibre tools for cleaning oil or wax finished surfaces will cause shorter intervals of maintenance and a higher consumption of oil or wax.

Ingredients

Carnauba wax, alcohol ester, water and sodium citrate

Precautions

Do not apply at temperature below 5°C or at relative humidity over 95%. Keep container sealed and out of reach of children. Do NOT empty into drains or watercourses. Allow unwanted paint to dry. Solid matter can be disposed of via the normal garbage collection service.

Safety

Even though non-toxic, Please keep out of reach of children.

Disclaimer

Natural paint products are usually better suited for people with allergies. However, it is advisable that individuals with chemical sensitivities test the products for compatibility.

This information sheet is given in good faith and to be used as a guideline for users to achieve the expected results. However, due to unpredictable circumstances beyond our control, the user is fully responsible for testing the product on the intended surface to ensure that it is suitable for one's requirements, NO LEGAL LIABILITY can be based on the content of these pages.

Made in Germany